






Type	AVK nr	VVS nr	DN mm	Tolerance mm	Enh. pr. palle	PN	Teoretisk vægt kg	Pris DKK	
Serie 631									
Universal og trækfast Supa Maxi™ lige kobling til alle rørtyper PN 16 Bolte og møtrikker i A4 Epoxy iht. DIN 30677-2 og GSK EPDM gummi, drikkevandsgod- kendt af NF-DVGW		631-071-00-63	14 3365.050	50	48-71	18	16	6,0	1.491
	631-091-00-63	14 3365.065	65	69-91	16	16	7,0	2.056	
	631-106-00-63	14 3365.080	80	82-106	14	16	7,5	1.896	
	631-133-00-63	14 3365.100	100	104-133	10	16	10	2.243	
	631-161-00-63	14 3365.125	125	132-159	12	16	12	3.664	
	631-188-00-63	14 3365.150	150	159-188	8	16	14	3.859	
	631-227-00-63	14 3365.200	200	193-227	6	16	25	6.143	
	631-257-00-63	14 3365.225	225	224-257	3	16	29	7.350	
	631-301-00-63	14 3365.250	250	266-301	4	16	33	7.545	
	631-356-00-63	14 3365.300	300	314-356	2	16	42	8.722	
	Serie 632								
Universal og trækfast Supa Maxi™ reduceret kobling til alle rørtyper PN 16 Bolte og møtrikker i A4 Epoxy iht. DIN 30677-2 og GSK EPDM gummi, drikkevandsgod- kendt af NF-DVGW DN 50-300				DN/DN	Tolerance-1 mm	Tolerance-2 mm			
	632-071-091-00-63	14 3366.050	50-65	48-71	69-91	16	6,8	2.028	
	632-071-106-00-63	14 3366.051	50-80	48-71	82-106	16	8,0	2.156	
	632-091-106-00-63	14 3366.065	65-80	69-91	82-106	16	8,5	2.156	
	632-106-133-00-63	14 3366.080	80-100	82-106	104-133	16	9,6	2.494	
	632-133-161-00-63	14 3366.100	100-125	104-133	132-159	16	11	3.044	
	632-133-188-00-63	14 3366.101	100-150	104-133	159-188	16	14	3.570	
	632-161-188-00-63	14 3366.125	125-150	132-159	159-188	16	14	3.733	
	632-188-227-00-63	14 3366.150	150-200	159-188	193-227	16	21	4.281	
	632-188-257-00-63	14 3366.151	150-225	159-188	224-257	16	28	5.147	
	632-227-257-00-63	14 3366.200	200-225	193-227	224-257	16	32	6.304	
	632-227-301-00-63	14 3366.201	200-250	193-227	266-301	16	33	6.829	
	632-257-301-00-63	14 3366.225	225-250	224-257	266-301	16	39	7.429	
	632-301-356-00-63	14 3366.250	250-300	266-301	314-356	16	41	8.859	
Enhed pr. palle som serie 631									
Serie 633									
Universal og trækfast Supa Maxi™ flangeadaptor til alle rørtyper PN 10/16 Bolte og møtrikker i A4 Epoxy iht. DIN 30677-2 og GSK EPDM gummi, drikkevands- godkendt af NF-DVGW DN 50-300		633-071-00-0063	14 3355.040	40/50	48-71	28	10/16	5,0	1.282
	633-091-00-0063	14 3355.050	50/65	69-91	24	10/16	6,0	1.621	
	633-106-00-0063	14 3355.080	80	82-106	18	10/16	7,0	1.786	
	633-133-00-0063	14 3355.100	100	104-133	20	10/16	8,0	2.145	
	633-161-00-0063	14 3355.101	100/125	132-159	18	10/16	10	3.318	
	633-188-00-0063	14 3355.150	150	159-188	13	10/16	11	3.216	
	633-227-00-0063	14 3355.200	200	193-227	10	10/16	19	4.768	
	633-257-00-0063	14 3355.225	225	224-257	4	10/16	24	6.572	
	633-301-00-0063	14 3355.250	250	266-301	3	10/16	27	6.572	
	633-356-00-0063	14 3355.300	300	314-356	2	10/16	36	7.414	

Type	AVK nr	VVS nr	DN mm	Tolerance mm	Enh. pr. palle	PN	Teoretisk vægt kg	Pris DKK	
Serie 634 Universal og trækfast Supa Maxi™ slutmuffe til alle rørtyper PN 16 Bolte og møtrikker i A4 Epoxy iht. DIN 30677-2 og GSK EPDM gummi, drikkevands- godkendt af NF-DVGW DN 50-300		634-071-00-0663 #)	14 3368.048	50	48-71	28	16	3,8	1.011
	634-071-00-0163 ##)	14 3368.050	50	48-71	28	16	3,8	1.011	
	634-091-00-0663 #)	14 3368.063	65	69-91	24	16	5,0	1.335	
	634-091-00-0163 ##)	14 3368.065	65	69-91	24	16	5,0	1.325	
	634-091-00-0363 ###)	14 3368.067	65	69-91	24	16	5,0	1.325	
	634-106-00-0663 #)	14 3368.078	80	82-106	21	16	5,5	1.403	
	634-106-00-0163 ##)	14 3368.080	80	82-106	21	16	5,5	1.403	
	634-106-00-0363 ###)	14 3368.082	80	82-106	21	16	5,5	1.403	
	634-133-00-0163 ##)	14 3368.100	100	104-133	15	16	7,2	1.524	
	634-133-00-0363 ###)	14 3368.102	100	104-133	15	16	7,2	1.524	
	634-161-00-0163 ##)	14 3368.125	125	132-159	12	16	8,4	2.589	
	634-161-00-0363 ###)	14 3368.127	125	132-159	12	16	8,4	2.589	
	634-188-00-0163 ##)	14 3368.150	150	159-188	8	16	10	2.627	
	634-188-00-0363 ###)	14 3368.152	150	159-188	8	16	10	2.627	
	634-227-00-0163 ##)	14 3368.200	200	193-227	6	16	16	4.327	
	634-227-00-0363 ###)	14 3368.202	200	193-227	6	16	16	4.327	
	634-257-00-0163 ##)	14 3368.225	225	224-257	5	16	23	5.583	
	634-257-00-0363 ###)	14 3368.227	225	224-257	5	16	23	5.583	
	634-301-00-0163 ##)	14 3368.250	250	266-301	3	16	23	5.730	
	634-301-00-0363 ###)	14 3368.252	250	266-301	3	16	23	5.730	
	634-356-00-0163 ##)	14 3368.300	300	314-356	2	16	29	6.648	
	634-356-00-0363 ###)	14 3368.302	300	314-356	2	16	29	6.648	
	# 1" BSP gevind, placeret parallelt med røret								
	## 1 1/4" BSP gevind, placeret parallelt med røret								
	### 2" BSP gevind, placeret parallelt med røret								
	Serie 635 Universal og trækfast Supa Maxi™ transitions- kobling til alle rørtyper PE 100 / PN 10 Bolte og møtrikker i A4 Epoxy iht. DIN 30677-2 og GSK EPDM gummi, drikkevandsgod- kendt af NF-DVGW DN 50-300		DN / PE-rør						
		635-071-00-2663	14 3363.063	50-63	48-71		10	4,5	1.285
		635-091-00-2663	14 3363.075	65-75	69-91		10	5,6	1.618
		635-106-00-2663	14 3363.090	80-90	82-106		10	6,0	1.832
		635-105-00-2663	14 3363.109	80-110	82-106		10	7,0	2.138
635-133-00-2663		14 3363.110	100-110	104-133		10	8,5	2.617	
635-161-00-2663		14 3363.159	125-160	132-159		10	16	3.103	
635-188-00-2663		14 3363.160	150-160	159-188		10	18	3.341	
635-227-00-2663		14 3363.200	200-200	193-227		10	27	4.678	
635-257-00-2663		14 3363.249	225-250	224-257		10	42	7.251	
635-301-00-2663		14 3363.250	250-250	266-301		10	45	7.399	
635-356-00-2663		14 3363.315	300-315	314-356		10	67	8.657	